

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO
10/674,955	09/30/2003	Terence Alan Reid	7134.US.O1	5288
7590 08/09/2006			EXAMINER	
Steven F. Weinstock			NOGUEROLA, ALEXANDER STEPHAN	
Abbott Laboratories D-377/AP6D			ART UNIT	PAPER NUMBER
100 Abbott Parl	k Road	1753		
Abbott Park, IL 60064-6050			DATE MAILED: 08/09/2006	

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)
	10/674,955	REID ET AL.
Office Action Summary	Examiner	Art Unit
	ALEX NOGUEROLA	1753
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with	the correspondence address
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING D. - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period of the second period for reply within the set or extended period for reply will, by statute any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICA 36(a). In no event, however, may a reply will apply and will expire SIX (6) MONTHS e, cause the application to become ABAN	TION. be timely filed from the mailing date of this communication. DONED (35 U.S.C. § 133).
Status		
1) Responsive to communication(s) filed on 30 Ju	<u>une 2006</u> .	
2a) ☐ This action is FINAL . 2b) ☑ This	s action is non-final.	
3) Since this application is in condition for allowa		
closed in accordance with the practice under E	Ex parte Quayle, 1935 C.D. 1	1, 453 O.G. 213.
Disposition of Claims	•	
4) ⊠ Claim(s) 1-3,5-14 and 16-21 is/are pending in 4a) Of the above claim(s) is/are withdray 5) □ Claim(s) is/are allowed. 6) ⊠ Claim(s) 1-3,5-14 and 16-21 is/are rejected. 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and/o	wn from consideration.	
Application Papers		
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 30 September 2003 is/a Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Example 11.	are: a) \boxtimes accepted or b) \square or displaying drawing(s) be held in abeyance tion is required if the drawing(s)	. See 37 CFR 1.85(a). is objected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the priority document application from the International Bureau * See the attached detailed Office action for a list	s have been received. s have been received in App rity documents have been red u (PCT Rule 17.2(a)).	lication No ceived in this National Stage
Attachment(s)		
1) Notice of References Cited (PTO-892)	4) Interview Sum	
 Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 		lail Date mal Patent Application (PTO-152)

DETAILED ACTION

Status of Objections and Rejections pending since the Office action of March 30, 2006 ("Office action")

1. All previous objections and rejections are withdrawn.

Response to Arguments

2. Applicant's arguments filed June 30, 2006 ("Amendment") have been fully considered but they are not persuasive.

<u>Rejections of claims 1-3, 5-9, 11, 13, 14, 16, 17, 20, and 21 as being unpatentable under 35 U.S.C. 103(a) over Urban</u>

Applicants assert that electrode 1 of Urban does not meet several of the requirements of claim 1 for the at least two conducting layers. See bottom of page 5 of

the Amendment, bridging to page 6. Assuming arguendo that Applicants are correct, these are moot points because the Examiner has not identified electrode 1 as an electrode corresponding to either of the claimed at least two conducting layers. Electrodes 2 and 3 in the embodiments of Figures 11 and 13 of Urban have been identified in the rejections as corresponding to the claimed at least two conducting layers and these electrodes do meet the requirements of the at least two conducting layers.

Page 3

Rejections of claims 1-3, 5-13, and 16-21 as being unpatentable under 35 U.S.C. 103(a) over Hyland

Applicants appear to assert that the edges in the electrochemical cell of Hyland do not collectively form a wall or walls of the passage. See page 7 of the Amendment. The Examiner respectfully disagrees. Hyland states, "The working electrodes is, for example, in the form of a continuous band around the wall(s) of the receptacle," "Furthermore, the step of creating a hole in the part containing the working electrode may eliminate the need for a separate step to activate the carbon, or other working electrode," and "This embodiment [Figure 3] of the invention is a multi-ring electrode which contains one or more further electrodes 10, 10' in addition to the working, counter and optionally reference electrodes" [emphasis added]." See page 8, lines 10-12;

page 4, lines 9-11; and page 12, lines 22-25 of Hyland. Indeed, if the conducting layers (electrodes) other the one at the bottom of the receptacle extended into the receptacle as a continuous layer or film they would block sample from flowing to the bottom of the receptacle and contacting all of the electrodes rendering the electrochemical cell inoperative. Applicants also assert that in Hyland the electro-active substance is not in contact with the working electrode. See page 7 of the Amendment. However, as stated on page 8 of the Office action

In Hyland the working electrode is not typically in contact with reagent so the "first electrode" of the previous paragraph would not typically be a working electrode. See bottom paragraph of page 10. However, barring a contrary showing, such as structural or compositional distinctions, the designation of an electrode as a "working" electrode (or counter electrode or reference electrode) is an arbitrary designation only signifying intended use. Hyland discloses that the working electrode and the counter electrode may be made from a variety of materials. The list of materials from which the working electrode may be made is actually included in the list of materials from which the counter electrode may be made. See page 8, second full paragraph and last paragraph, bridging to page 9. Indeed, the working electrode may have an Ag/AgCl layer, which is commonly and traditionally only used for reference electrodes. See page 8, lines 20-23.

Rejections of claims 2, 18, and 19 as being unpatentable under 35 U.S.C. 103(a) over Urban in view of Fritsch

Applicants' arguments rely in part on their arguments against Urban, which have been addressed above. Applicants also argue, "Fritsch et al. does not disclose or suggest that the cavity electrode system described therein has a working electrode in

Application/Control Number: 10/674,955 Page 5

Art Unit: 1753

contact with at least one reagent." See page 8 of the Amendment. However, this was acknowledged in the Office action. Fritsch was only cited for available manufacturing techniques to make the cell volume or dimensions within the claimed ranges. In response to applicant's arguments against the references individually, one cannot show nonobviousness by attacking references individually where the rejections are based on combinations of references. See *In re Keller*, 642 F.2d 413, 208 USPQ 871 (CCPA 1981); *In re Merck & Co.*, 800 F.2d 1091, 231 USPQ 375 (Fed. Cir. 1986).

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Application/Control Number: 10/674,955 Page 6

Art Unit: 1753

4. The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

- 1. Determining the scope and contents of the prior art.
- 2. Ascertaining the differences between the prior art and the claims at issue.
- 3. Resolving the level of ordinary skill in the pertinent art.
- 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
- 5. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).
- 6. Claims 1-3, 5-9, 11, 13, 14, 16, 17, 20, and 21 are rejected under 35 U.S.C. 103(a) as being unpatentable over the English language translation of Urban (WO 90/12314 A1) ("Urban").

Addressing claim 1, Urban discloses an electrochemical cell comprising an

Application/Control Number: 10/674,955

Art Unit: 1753

insulating substrate (5 in Figures 11 and 13) and a plurality of layers (Figures 11, and 13), the layers comprising at least two conducting layers (2 and 3), wherein one of the conducting layers is a first electrode (2 – top of page 16 and bottom of page 17 and first full paragraph on page 18), and at least two insulating layers (4, 4' in Figures 11, 13), wherein at least one of the at least two insulating layers (Figures 11, and 13) is interposed between the at least two conducting layers (Figure 1), wherein each major surface of each conducting layer is in contact with a major surface of the insulating substrate or a major surface of at least one of the at least two insulating layers (Figures 11 and 13), a passage being formed through the at least two conducting layers and the at least two insulating layers to expose edges of the at least two conducting layers and the at least two insulating layers, the edges collectively forming a wall or walls of the passage, the exposed edges of the at least two conducting layers forming the working electrode and a second electrode of the electrochemical cell (implied by Figures 11 and 13).

As for the first electrode being a working electrode, barring a contrary showing, such as structural or compositional distinctions, the designation of an electrode as a "working" electrode (or counter electrode or reference electrode) is an arbitrary designation only signifying intended use. Furthermore, although the descriptions of Figures 11, and 13 do not label the first electrode (electrode 2) as a working electrode, one with ordinary skill in the art at the time of the invention would understand that it is a working electrode because with regard to related Figure 8 the description of Figure 8 states that the first electrode (electrode 2) is a measurement electrode (top of page 16)

Application/Control Number: 10/674,955

Art Unit: 1753

and with regard to Figures 11 and 13, closely related Figure 2 identifies the first electrode (electrode 2) as a measurement electrode (first full paragraph on page 18) and, in fact, whenever the function of the first electrode (electrode 2) is identified in a description of an embodiment it is identified as a working electrode, while electrode 3 is identified as a counter electrode and electrode 1 as a reference electrode (see, for example, page 14).

As for having the working electrode in contact with at least one reagent, it would have been obvious to one with ordinary skill in the art at the time of the invention to do so because Urban broadly discloses that the electrochemical cell may be used as a biosensor and states," For this purpose, enzymes are immobilized on one of the electrodes" (page 19, second full paragraph) and since the working electrode will measure the product(s) of the reagent reaction with the sample, by having the reaction layer on the working electrode the response time will be faster and more accurate than if the reaction layer is located elsewhere as the reagent reaction products will have less distance to travel and less chance of being impeded by diffusion effects or chemical interferants.

It should be noted that the examiner has broadly construed the word "contact" in claim 1, especially in the last four lines of the claim, to mean direct or *indirect* contact. In Applicants' embodiments of Figures 1 and 5 a major surface of the working electrode contacts a major surface of the conducting layer or insulating substrate through a reagent layer. In Applicants' Figure 1 note element 20 and for Figure 5 see Applicants' specification page 9, lines 22-27.

Addressing claim 2, for the additional limitations of this claim see Figures 8, 11,

Page 9

13

Addressing claim 3, for the additional limitations of this claim see Figures 11 and

13

Addressing claims 5-7, for the additional limitations of these claims consider that

they are intended uses, which barring a contrary showing, the electrodes in the

electrochemical cell of Urban is capable of. The cells in Figures 8, 11, 13 comprise

three electrodes: a working electrode (2), a counter electrode (3), and a reference

electrode (1). However, the counter electrode is capable of being used as a second

working electrode to measure the concentration of the same or a different analyte as the

other working electrode.

Addressing claims 8, and 9, for the additional limitations of these claims see

page 14, second full paragraph (although this passage is in reference to Figures 4 and

5, the intended uses of the these electrodes appears to apply to all of the figures).

Addressing claim 11, for the additional limitations of this claim see Figures 11

and 13.

Addressing claim 13, for the additional limitations of this claim see Figures 11 and 11

Addressing claim 14, for the additional limitations of this claim see Figure 13.

Note that the examiner is broadly construing "irregular shape" to include an electrochemical cell profile with a passage defined by non-parallel walls and a non-monotonically changing spacing between them.

Addressing claims 16 and 17, for the additional limitations of these claims see the last paragraph on page 11. For claim 17 note again, as stated in the rejection of claim 1, "by having the reaction layer on the working electrode the response time will be faster and more accurate than if the reaction layer is located elsewhere as the reagent reaction products will have less distance to travel and less chance of being impeded by diffusion effects or chemical interferants."

Addressing claim 20, for the additional limitation of this claim see Figures 8, 11, and 13. Let the insulating substrate instead be the insulating layer between electrodes 2 and 3, let the top insulating layer 4 and the bottom insulating layer 4 be the at least two insulating layers of claim 1 (after all, an "insulating layer' is also an "insulating substrate").

Art Unit: 1753

Addressing claim 21, for the additional limitation of this claim see Figures 8, 11, and 13.

7. Claims 1-3, 5-13, and 16-21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hyland (WO 03/056319 A2) ("Hyland").

Addressing claim 1, Hyland discloses an electrochemical cell comprising an insulating substrate (bottom layer 7 in Figures 2 and 3 and bottom layer in Figure 7) and a plurality of layers (Figures 2, 3, 7), the layers comprising at least two conducting layers ((5,6,9,10,10') Also see page 12:30 – page13:2, which discloses up to ten electrodes), and wherein one of the conducting layers is a first electrode (6), the first electrode in contact with at least one reagent ((8) Figures 2, 3, and 7), and at least two insulating layers (Figures 2, 3, and 7), wherein at least one of the at least two insulating layers is interposed between the at least two conducting layers (Figures 2, 3, and 7), wherein each major surface of each conducting layer is in contact with a major surface of the insulating substrate or a major surface of at least one of the at least two insulating layers (Figures 2, 3, and 7), a passage being formed through the at least two conducting layers and the at least two insulating layers, the edges collectively forming a wall or walls of the passage, the exposed edges of the at least two conducting

layers forming the working electrode and a second electrode of the electrochemical cell (implied by page 8, lines 10-12; page 4, lines 9-11; and page 12, lines 22-25 of Hyland, which discloses band or ring electrodes or a hole through an electrode).

In Hyland the working electrode is not typically in contact with reagent so the "first electrode" of the previous paragraph would not typically be a working electrode. See bottom paragraph of page 10. However, barring a contrary showing, such as structural or compositional distinctions, the designation of an electrode as a "working" electrode (or counter electrode or reference electrode) is an arbitrary designation only signifying intended use. Hyland discloses that the working electrode and the counter electrode may be made from a variety of materials. The list of materials from which the working electrode may be made is actually included in the list of materials from which the counter electrode may be made. See page 8, second full paragraph and last paragraph, bridging to page 9. Indeed, the working electrode may have an Ag/AgCl layer, which is commonly and traditionally only used for reference electrodes. See page 8, lines 20-23.

Addressing claim 2, for the additional limitations of this claim see Figures 2, 3, and 7 and again note page 12:30 – page13:2, which discloses up to ten electrodes.

Addressing claim 3, for the additional limitations of this claim see Figures 2 and 3 and again note page 12:30 – page13:2, which discloses up to ten electrodes.

Addressing claim 5, for the additional limitation of this claim see page 6:1-3 and page 12:20-25.

Addressing claims 6 and 7, for the additional limitations of these claims see page 13, first full paragraph.

Addressing claims 8 and 9, for the additional limitations of these claims see page 12:1-28.

Addressing claim 10, for the additional limitation of this claim see page 12:6-8.

Addressing claim 11, for the additional limitation of this claim see Figures 2, 3, and 7.

Addressing claim 12, for the additional limitation of this claim see page 7, first full paragraph. Let, for example, the passageway have a depth of 50 μ m, a length of 0.1 mm, and a width of 0.1 mm (square cross-section from top view). Then the volume will be 500,000 μ m³, which equals 0.0005 micro liter.

Art Unit: 1753

Addressing claim 13, for the additional limitation of this claim see Figures 2, 3, and 7 and page 7, first full paragraph, which implicitly discloses a circular, or square, or rectangular cross-section from a top view.

Addressing claims 16 and 17, for the additional limitations of these claims see page 24:1-11 and

Addressing claim 18, for the additional limitation of this claim see page 22:20-24 – page 23:5.

Addressing claim 19, for the additional limitation of this claim see page 23:10-14.

Addressing claim 20, for the additional limitation of this claim see Figure 2. Let the insulating substrate instead be the insulating layer between electrodes 6 and 9, let the insulating layer between electrodes 5 and 9 be the insulating layer of claim 1 that separates at least two conducting layers, and let the insulating layer directly above electrode 7 be the second of the at least two insulating layers of claim 1.

Addressing claim 21, for the additional limitation of this claim see Figures 2 and 3.

8. Claims 12, 18, and 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over the English language translation of Urban (WO 90/12314 A1) ("Urban") as applied to claims 1-3, 5-9, 11, 13, 14, 16, 17, 20, and 21 above and further in in view of Fritsch et al. (US 2003/0015422 A1) ("Fritsch").

Addressing claim 12, although Urban clearly discloses small dimensions for the cell (claim 15 and page 17, last paragraph, bridging to page 18), Urban does not mention a cell volume not exceeding 1 microliter.

Fritsch discloses an electrochemical cell comprising an insulating substrate and alternating layers of conductor and insulator (see the abstract and Figure 6), which also reads on Applicants' claim 1, except for reagent in contact with the working electrode. Fritsch further discloses techniques for making a cell volume down to 0.00000849056 mircoliter. See paragraph [106], using a circular cavity with a radius of $6.5~\mu m$ and a depth of $8~\mu m$.

Barring evidence to the contrary, such as unexpected results, in light of Fritsch, to reduce the electrochemical cell volume in Urban to below 1 micro liter is just scaling down the cell for a smaller expected sample volume range.

Addressing claims 18 and 19, although Urban clearly discloses small dimensions for the cell (claim 15 and page 17, last paragraph, bridging to page 18), Urban does not mention the claimed thickness ranges.

Fritsch discloses an electrochemical cell comprising an insulating substrate and alternating layers of conductor and insulator (see the abstract and Figure 6), which also

Art Unit: 1753

paragraph [0106].

reads on Applicants' claim 1, except for reagent in contact with the working electrode. Fritsch further discloses techniques an embodiment having a cavity with a depth of 8 µm through two conducting layers and two insulating layers. Thus, Fritsch discloses conducting layers and insulating layers that do not exceed 100 micrometers. See

Barring evidence to the contrary, such as unexpected results, in light of Fritsch, to have a conducing layer or an insulating layer within the claimed respective ranges is just scaling down the cell for a smaller expected sample volume range.

9. Any inquiry concerning this communication or earlier communications from the examiner should be directed to ALEX NOGUEROLA whose telephone number is (571) 272-1343. The examiner can normally be reached on M-F 8:30 - 5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, NAM NGUYEN can be reached on (571) 272-1342. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/674,955 Page 17

Art Unit: 1753

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Alex Noguerola Primary Examiner

AU 1753

August 6, 2006